

REPIC

Renewable Energy &
Energy Efficiency
Promotion in
International
Cooperation



Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Staatssekretariat für Wirtschaft SECO
Direktion für Entwicklung und Zusammenarbeit DEZA


Bundesamt für Umwelt BAFU

Bundesamt für Energie BFE

Biogas production of coffee pulp & waste waters

Reto Steiner, EBP, 20.6.2011






Anaerobic digestion

- Greenhouse gas emissions from pulp & waste waters could be reduced, as much as pollution of local rivers or lakes, unpleasant odours & attraction of flies and insects.

→ With adequate storage, digestion and composting.



90% less emissions due to pulp treatment possible



Anaerobic digestion of Pulp

SFOE study in 2002/2003 conducted by HSW:

- Pulp is an appropriate substrate for anaerobic digestion.
- Pulp can be digested as mono-charge.
- There are sufficient nutrients in the pulp (C:N:P = 250:10:1)
- The anaerobic digestion is not inhibited by pulp.



REPIC

Renewable Energy &
Energy Efficiency
Promotion in
International
Cooperation

Anaerobic digestion of Pulp

- Biogas production, batch: 0.38 m³ biogas/kg oTS , ~60 m³ Biogas/m³ pulp.
- Continuous digester: until 2 x more gas, test has to be repeated.



Mesophile Batch Tests

Originale Pulpa:

TS 162 kg/m³

oTS = 92.8 % der TS

TN = 2.05 kg/m³

TP = 0.21 kg/m³

C : N : P = 250 : 10 : 1

pH = 5.4

Temperatur: 36 °C


TS Abbau: 50 – 64%

oTS Abbau: 60 – 72 %




zhaw, U. Baier

Zur Biogasproduktion
hat's ausreichend
Nährstoffe



Die Pulpa hemmt den
anaeroben Abbau nicht.



REPIC Biogas project-study (axpo, 2010)

- Biogas plant at „Beneficio Santo Domingo“, Costa Rica.
- Input: Pulp with mucilage: ~8'000 t/y
- Pulp is produced during processing period: from oct-march.



REPIC Biogas project-study (axpo, 2010)



Storage

- Low pH < 5.0 prevents anaerobic methane formation and favours lactic acid bacteria (silage).
- Oxygen limitation, low O₂ prevents Carbon degradation and energy losses.
- Coverage and rainfall protection to prevent leaching of silage juices.

AD Dimensioning

Mesophilic 32 – 38 °C

HRT = 16 – 30 days

V.S. Load: 5 kg/m³*d

V.S. Rate: 4.2 kg/m³*d

Biogas Rates:

- 400 NL / kg V.S.

- 60 m³ / m³ pulp

Reactor type:

- Plug flow /recirculation

- Stirred Tank Reactor

Substrate prone to flotation & sedimentation

Products

Biogas: 68 % CH₄

Digestate:

< 15 % D.S., requires dewatering

Post composting:


- > 8 weeks

- high demand for turn-over & aeration.

- demand for structural additives (straw, wood).


Liquid fertiliser:

- High TN, 2 g/l



zhaw, U. Baier

REPIC Biogas project-study (axpo, 2010)



REPIC Biogas project-study (axpo, 2010)

Results

- Pulp must be stored temporarily to extend operation period of biogas plant.
- Silage of raw pulp is a solution to preserve pulp and to have available substrate for the digester during ~ 8-9 months.
- Plant is not economic (with only 8 months operation, 8 ct.\$ paid for electricity, substitution of cheap wood)
- It needs other substrates → Operation during 365 days.
- Electricity must be sold to a better price.


zhaw, U. Baier



Probe	Pulpa frisch	Open air	Open air	Silage
Alter	Wenige Tage	2 Wochen	2 Monate	3 Monate
pH	3.8	8.8	9.0	5.1

Anaerobic digestion of waste water

- **Waste water from demucilaging is adequate for anaerobic digestion:**
 - Contain mucilage (aguas mieles / agua con mucilago)
 - High organic load, high suger content
 - Also contain pectins and organic acid
- **Operation is more delicate than only with pulp because of acidification (pH, results in low CH₄ content).**



REPIC

Renewable Energy &
Energy Efficiency
Promotion in
International
Cooperation

Anaerobic digestion of waste water

- **Costa Rica: Upflow anaerobic sludge blanket (UASB) reactors have been built from 1997-2001.**
- **In 2005: 9 UASB-reactors in operation.**
- **Biogas is used in ovens with wood & parchment for coffee-bean drying.**
- **Biogas production: 1.3 m³ Biogas / m³ waste water with a removal efficiency of 80%.⁽¹⁾**
- **Problems: inefficient production of biogas, technical problems, insufficient operation & capacitation → not optimized process.**
- **High costs for construction & operation are not cost-effective.**
- **The reactors are used to comply with the permissible value.**



REPIC
 Renewable Energy &
 Energy Efficiency
 Promotion in
 International
 Cooperation


Schweizerische Eidgenossenschaft
 Confédération suisse
 Confederaziun Svizra
 Confederaziun Tudestga

Staatsekretariat für Wirtschaft SEKO
 Dirección für Entwicklung und Zusammenarbeit DEZA
 Bundesamt für Umwelt BAFU
 Bundesamt für Energie BFE

*(1): Result from Beneficio San Juanillo, Costa Rica, Cosecha 96/97:
 Biogas production per day: 540 m³ Biogas / 400 m³ waste water*

Conclusion (I)

- **High seasonality (waste generation & energy use): 3-4 months is a important disadvantage.**
- **Residues require special attention (seasonal peak loads, quick biodegradation).**
- **Silage offers low carbon loss & low greenhouse gas emissions.**
- **Co-Digestion of coffee pulp and other biowastes is required to allow a continuous operation.**
- **Appropriate/economic technique for pulp with waste water:
Stirred tank reactor.**



REPIC
Renewable Energy &
Energy Efficiency
Promotion in
International
Cooperation

Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Staatsekretariat für Wirtschaft SECO
Direktion für Entwicklung und Zusammenarbeit DEZA
Bundesamt für Umwelt BAFU
Bundesamt für Energie BFE

Conclusion (II)

- Electricity production only interesting for large processing plants.
- Biogas for drying / cooking with less sophisticated digester.
- Substitution of wood & electricity often is little cost-effective (due to low energy prices).
- In 2008 there was only very restricted willingness of coffee producers to invest in environmental technology due to the instable market situation.
- Economic benefit has to be proven today due to other surrounding conditions.



REPIC
Renewable Energy &
Energy Efficiency
Promotion in
International
Cooperation